





- More Durability and Hygiene.
- High Operating Efficiency.
- Motor designed with a High Cooling Effect.
- Designed for Wide Voltage Operation.
- Sturdy and Compact.



Vision, Mission and Values

To be the industry leader providing best-in-class fluid management solutions to individual and institutional customers and societies in our chosen markets.

We will achieve this through our dedicated efforts to enhance the welfare of all our stakeholders and by living by our values of **Commitment, Reliability** and **Innovation.**



ABOUT C.R.I.

C.R.I. ranks high among the world's fastest-growing fluid management solutions provider with a wide global presence. C.R.I. offers Pumps, Motors, IoT Driven Pumps, IoT Drives & Controllers, Pipes, Wires & Cables, Solar Pumps and Controllers to meet the pumping needs of its wide customer base.



60+ Years of Engineering Expertise





Manufacturing Units around the World



30000 + Outlets to serve our Customers



9000+
Products for various applications



1500+Service Centres to support our Customers



16 TimesEEPC Award Winner for Export Excellence



8 TimesNEC Award Winner for Energy Savings



Fludyn Advanced Technology Centre Recognized by Ministry of Science & Technology, Govt. of India.

C.R.I. PIPES - C.R.I.'s state-of-the-art manufacturing facility at Ahmedabad & Hosur produces all kinds of best quality PVC, UPVC, CPVC Pipes & Fittings. The plants are empowered with fully automated machines that control the manufacturing process.

C.R.I. WIRES & CABLES - C.R.I.'s Wires & Cables are manufactured at its state-of-the-art manufacturing facility. The systems at the manufacturing facility are ISO-9001 certified and the products manufactured to meet the relevant standards.

C.R.I. SOLAR PUMPING SYSTEM - C.R.I. manufactures sustainable Solar Pumping Systems designed to work with best in class efficiency. With this C.R.I. emphasizes its focus towards greener technology.





80mm Borewell Submersible Pumpset- ZUNO LITE Series

C.R.I. ZUNO Lite 80 mm Borewell submersible motors are pre-filled with non-toxic liquid for best performance in low voltage and high efficiency. The pump is firmly coupled to a submersible electric motor which operates submerged beneath the surface of water. The optimal design of impeller and diffuser enables the best possible hydraulic efficiency. Built-in check valve prevents back flow and reduces the risk of water hammering. All vital components of these pumps are made up of corrosive resistance thermoplastic and the shaft is of SS 431.

SALIENT FEATURES

• More durability and hygiene • High operating efficiency • Designed for wide voltage operation • Additional intermediate bearing in higher stage pumps.

APPLICATION

• Gardens • Irrigation • Farms • Industrial.

SPECIFICATIONS	80MM ZUNO LITE
Power range	0.75 kW & 1.1 kW (1.0 HP & 1.5 HP)
Speed	2800 RPM
Version	Single Phase 220V, 50Hz, A.C. Supply
Maximum total head	70 Metre
Maximum flow rate	1.5 LPS (5.40 m³/hr)
Maximum outer diameter	78 mm
Thrust load	650 LBS
Minimum cooling flow along the motor	0.15 m/sec
Method of starting	Capacitor Start Capacitor Run (CSCR)
Maximum starts per hour	20 times
Nominal outlet size	32 mm

PERFORMANCE CHART

80mm BOREWELL SUBMERSIBLE PUMPSET - ZUNO LITE Series

RA		

Model	kW	HP	age	Outlet Size in	m³/hr	0	0.72	1.08	1.44	1.80	2.16	2.52	2.88	3.24
Model	I KVV	'''	Ste	mm	lps	0	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90
CRI3R-31/1/17	0.75	1.0	17	32	Head in Metres	70	66	64	62	55	49	44	34	24

Model	kW	HP	Stage			0	0.72	1.44	2.16	2.88	3.60	4.32	5.04	5.40
Model	KVV	111	Stg	Size in mm	lps	0	0.20	0.40	0.60	0.80	1.00	1.20	1.40	1.50
CRI3R-33/1/10	0.75	1.0	10	32	es es	37	35	33	32	30	28	23	18	13
CRI3R-33/1/12	0.75	1.0	12	32	et g	44	42	40	39	36	31	25	20	14
CRI3R-33/1.5/15	1.1	1.5	15	32	H ≥	59	58	56	53	49	41	33	22	17

MATERIAL OF CONSTRUC	TION - PUMP
Part Name	Material
Check valve housing	Cast iron
Outer shell	Stainless Steel
Impeller	Noryl
Diffuser chamber	Noryl
Counter thrust pad	Hylem
Intermediate bearing (Sleeve / Bush)	SS - 304 / NBR
Suction inter connector	Cast iron
Pump shaft	SS - 304
Coupling	SS - 410
Outer shell Impeller Diffuser chamber Counter thrust pad Intermediate bearing (Sleeve / Bush) Suction inter connector Pump shaft	Stainless Steel Noryl Noryl Hylem SS - 304 / NBR Cast iron SS - 304

MATERIAL	OF CONSTRUCTION - MOTOR
Part Name	Material
Stator shell	SS 304
Shaft seal	Nitrile Butyl Rubber / Mechanical Seal
Motor base	Cast iron
Motor Shaft	SS - 431
Bearing	SS Ball Bearing
Snap Ring	SS - 316



\$ CATERS TO DIVERSE SEGMENTS \$

WATER & WASTE WATER | SOLAR | PROCESS INDUSTRIES | SEWAGE & EFFLUENT TREATMENT PLANTS
HVAC | FIRE FIGHTING | METAL & MINING | FOOD & BEVERAGE | AGRICULTURE | RESIDENTIAL





● TOLL FREE 1800 121 1243 ● www.crigroups.com ● chatbot: +91 9500401115